

Serial No. 09/540,319

In the Claims:

1. (Previously amended): A medical diagnostic device for measuring an analyte concentration of an electrically conductive biological fluid, comprising a multiplayer structure having a first layer and a second layer sandwiching an intermediate layer,
 - (a) the first and second layers each comprising an insulating sheet, having a conductive surface adjoining the intermediate layer,
 - (b) the intermediate layer being an insulating layer with a cutout, having a first end and a second end, which, together with the first and second layers, defines a flow channel to permit the sample to flow from the first end to the second end,
 - (c) the flow channel comprising (i) a dry reagent on the conductive surface of one of the layers for reacting with the sample to yield a change in an electrical parameter that can be related to the analyte concentration of the fluid and (ii) an electrochemical cell, within which the electrical parameter is measured,
 - (d) a first one of the conductive surfaces having a first insulating pattern scored into it to divide the first conductive surface into two regions, insulated from each other, whereby sample that flows across the pattern provides a conductive path from the first end to the second end.
2. (Original): The device of claim 1, in which the first end of the cutout is at a first edge of the intermediate layer and the second end is at a second edge of the intermediate layer, opposite the first edge.
3. (Original): The device of claim 1, in which the dry reagent is on the conductive surface of the first layer and the insulating pattern is scored into the conductive surface of the second layer.
4. (Original): The device of claim 1, in which sample that enters the flow channel at the first end flows through the electrochemical cell, before it reaches the first insulating pattern.
5. (Original): The device of claim 1, in which the biological fluid is blood and the analyte being measured is glucose.

Serial No. 09/540,319

6. (Original): The device of claim 1, in which the first and second layers each comprise metallized thermoplastic sheets.
7. (Original): The device of claim 1, in which the intermediate layer comprises a thermoplastic sheet having adhesive on both surfaces for adhering to the first and second layers.
8. (Original): The device of claim 1, in which the reagent on the conductive surface comprises a buffer, a mediator, and an enzyme.
9. (Original): The device of claim 1, in which the flow channel is a capillary channel and the insulating pattern scored into the conductive surface has at least one serration within the flow channel.
10. (Original): The device of claim 9, in which the insulating pattern has at least one serration within the flow channel pointing toward each end of the channel.
11. (Original): The device of claim 1, further comprising a second insulating pattern scored into the conductive surface of the scored layer between the first end and the first insulating pattern to divide the scored layer into three regions, insulated from each other.
12. (Original): The device of claim 11, in which sample that enters the flow channel at the first end reaches the second insulating pattern before it flows through the electrochemical cell.
13. (Original): The device of claim 1, further comprising electrical circuit means for detecting the flow of fluid through the flow channel.

Claims 14-16 (Withdrawn):